

R-PDD18-70-XS RawlDriver 18V cordless drill / driver, in carton box

The 18V drill driver allows you to use a high torque of 70 NM to drive screws depending on the hardness of the material.



Product information

Features and benefits

- Powerful brushless motor ensures high efficiency of the mechanism and increases the life time of the power tool
- Rubberised, profiled handle increases grip and user ergonomics
- 16 + 1 positions of the clutch allows optimal selection of torque for driving of bolts and screws of different sizes depending on the type of substrate
- The single-sleeve 13 mm drill chuck makes it easy to install all accessories
- Planetary gear parts are made of high quality steel to increase the tool life-time
- Compact design and lightweight construction reduces fatigue during long-term use
- LED illuminates the work place to increase user comfort and safety

Applications

- Timber constructions: tightening screws up to 6 mm
- Metal constructions: assembly of metric screws (up to M6)
- Frame pins and others up to 14 mm (e.g. FF1, 4ALL)
- Drilling sheets with a thickness of 2 mm to 10mm

Corresponding products

- R-PTK Construction screw with wafer head and partial thread
- R-PVS Construction screw with countersunk head and full thread

Base materials

- Metal Sheet & Profiles
- Stainless Steel
- Plastics
- · Decking board
- Wood
- Chipboard

Set includes

- R-PDD18-70 RawlDriver
- · Manual user instructions



Product commercial data

| Index | Battery voltage | Battery | | Char- ging ti- me | Max. co- | Number of clutch set- tings | Chuck | Rota- tional speed 1st ge- ar | Rota- tional speed 2nd ge- ar | onal drilling beed diame- d ge- ter in | diame- | Tool weight without battery | | Outer weight | EAN |
|---------------|--------------------|-------------------------|-------------------------|-------------------------|----------|---|--------|---|---|--|--------|--------------------------------------|------|-----------------|-----------------------|
| | [v] | | | | | | [mm] | [r/min] | [r/min] | [mm] | [mm] | [kg] | kg | kg | |
| R-PDD18-70-XS | 18 | brak w zesta- wie | brak w zesta- wie | brak w zesta- wie | 70 | 16 + 1 | 2 - 13 | 0 - 550 | 0 - 2000 | ø 40 | ø 13 | 1,3 | 1.50 | 1.50 | 590667 55060 81 |