


Technical data sheet



Steel	Chromium steel 34CrNiMo6
Carbide	WC-Cobalt Grade CTM17 BC
Surfacing	Pin shooting
Carbide tip design	Full carbide tip 3 edges with centering point
Tip angle	135° +/- 2°
Process and design of flute	Fully ground half round flute
Attachement	Compatible SDS+
Hardness	46 à 52 HRC
Standard	Produit certifié PGM
Origine	France

Powertools	SDS+ hammer less than 5Kg
Materials	Concrete, reinforced concrete stone, full brick

Stocked range

Product Code	Description			Logistic data		EAN
	Ø [mm]	L [mm]	L1 [mm]	Quantity [pcs]	Weight [kg]	
RT-SDSR-5/110	5	110	50	1	0,039	5906675115269
RT-SDSR-5/160	5	160	100	1	0,3	5906675046006
RT-SDSR-5/210	5	210	150	1	0,042	5906675115276
RT-SDSR-6/110	6	110	50	1	0,3	5906675047713
RT-SDSR-6/160	6	160	100	1	0,3	5906675046013
RT-SDSR-6/160B12	6	160	100	12	0,57	5906675063560
RT-SDSR-6/210	6	210	150	1	0,3	5906675046020
RT-SDSR-6/260	6	260	200	1	0,3	5906675046037
RT-SDSR-6/310B12	6	310	250	12	0,884	5906675063591
RT-SDSR-7/160	7	160	100	1	0,3	5906675047737
RT-SDSR-8/110	8	110	50	1	0,3	5906675047720
RT-SDSR-8/160	8	160	100	1	0,3	5906675046044
RT-SDSR-8/160B12	8	160	100	12	0,679	5906675063577
RT-SDSR-8/210	8	210	150	1	0,3	5906675046051
RT-SDSR-8/260	8	260	200	1	0,3	5906675046068
RT-SDSR-8/310	8	310	250	1	0,3	5906675046075
RT-SDSR-8/310B12	8	310	250	12	0,97	5906675063607
RT-SDSR-8/460	8	460	400	1	0,3	5906675046082
RT-SDSR-10/160	10	160	100	1	0,3	5906675046099
RT-SDSR-10/160B12	10	160	100	12	1	5906675063584
RT-SDSR-10/210	10	210	150	1	0,3	5906675046105
RT-SDSR-10/260	10	260	200	1	0,3	5906675046112
RT-SDSR-10/310	10	310	250	1	0,3	5906675046136
RT-SDSR-10/310B12	10	310	250	12	1	5906675063614
RT-SDSR-10/460	10	460	400	1	0,3	5906675046143
RT-SDSR-12/160	12	160	100	1	0,3	5906675046150
RT-SDSR-12/210	12	210	150	1	0,3	5906675046167
RT-SDSR-12/260	12	260	200	1	0,3	5906675046174
RT-SDSR-12/310	12	310	250	1	0,3	5906675046181
RT-SDSR-12/460	12	460	400	1	0,3	5906675046198
RT-SDSR-14/210	14	210	150	1	0,3	5906675046204
RT-SDSR-14/260	14	260	200	1	0,3	5906675046211
RT-SDSR-14/310	14	310	250	1	0,3	5906675046228
RT-SDSR-14/460	14	460	400	1	0,3	5906675046235
RT-SDSR-16/210	16	210	150	1	0,3	5906675046242
RT-SDSR-16/260	16	260	200	1	0,3	5906675046259
RT-SDSR-16/310	16	310	250	1	0,3	5906675046266
RT-SDSR-16/460	16	460	400	1	0,3	5906675046273
RT-SDSR-18/310	18	310	250	1	0,3	5906675046280
RT-SDSR-20/310	20	310	250	1	0,3	5906675046297