

Express Anchor Nails

Metal anchor made of galvanised steel for multiple use for non-structural applications in concrete



Product information

Features and benefits

- Multiple use for non-structural applications
- Large head - easy to pound in with a hammer or using the setting tool
- Additional expansion via cone and clip
- Shallow drill hole depth
- No screwing required
- Use in concrete, brickwork, blockwork & stone
- Secures wooden battens & sub frame to walls
- High quality spring steel

Applications

- Ideal for the attachment of various timber frames, battens and other similar materials

Base materials

Approved for use in:

- Concrete

Also suitable for use in:

- Cracked concrete C20/25-C50/60
- Non-cracked concrete C20/25-C50/60
- Reinforced concrete
- Unreinforced concrete
- Concrete
- Solid Brick

Product information

Product Code	Diameter	Length	Quantity [pcs]
	d	L	
	[mm]	[m]	
R-EXP-06040/200	6	40	200
R-EXP-06060/200	6	60	200
R-EXP-06080/200	6	80	200
R-EXP-08070/100	8	70	100
R-EXP-08090/100	8	90	100
R-EXP-08110/100	8	110	100
R-EXP-08130/100	8	130	100

Product commercial data

Product Code	Diameter [mm]	Length [mm]	Quantity [pcs]			Weight [kg]			Bar Codes
			Box	Outer	Pallet	Box	Outer	Pallet	
R-EXP-06040/200	6	40	200	4800	134400	0.81	19.3	571.3	5906675329802
R-EXP-06060/200	6	60	200	2400	67200	1.26	15.1	453.4	5906675329819
R-EXP-06080/200	6	80	200	2400	67200	1.59	19.1	565.1	5906675329826
R-EXP-08070/100	8	70	100	2400	57600	1.14	27.3	684.3	5906675329833
R-EXP-08090/100	8	90	100	1200	28800	1.47	17.6	452.5	5906675329840
R-EXP-08110/100	8	110	100	1200	28800	1.78	21.4	543.5	5906675329857
R-EXP-08130/100	8	130	100	1200	33600	1.75	21.0	618.0	5906675383729