

R-RAWL-PN-3490 Pneumatic framing nailer

Pneumatic paper strip nailer for timber framing, roofing and other timber applications



Certificate



Product information

Features and benefits

- Nail range from 50mm to 90mm for wide range of applications
- Adjustable exhaust port is an important safety feature when operating in areas where other persons may be affected by the exhausted air and particles
- Depth of drive adjustment provides fine tuning installation depth in any type of substrate material and application
- Removable no mark nose for protecting the timber surface. Especially important when securing timber cladding or facades
- More powerful than gas powered equivalent of the same specification. Up to 10% more power ensures outstanding performance in all applications and timber types

Applications

- Timber frame stud work in timber framing industry
- Installation of battens and sheathing in roof construction
- Installation of wooden facades
- Installation of timber flooring and terraces

Corresponding products

- SPG-DPK paper collated nails nails without fuel cells
- SPG-DRG paper collated nails nails without fuel cells
- SPG-DRK paper collated nails nails without fuel cells

Base materials

- Timber
- Plywood
- Chipboard
- Wood

Set includes

- R-RAWL-PN-3490 Pneumatic framing nailer
- Spare gasket set
- Operating and Safety manual
- Safety glasses and ear plugs
- Case



Product commercial data

Index	Power source	Magazine type	Magazine capacity	Magazine angle	WEIGHT	Faster diameter range	Faster length range	Noise level	Maximum pressure	Operating pressure	Faster type	Dimensions	Box weight	Outer weight	EAN
			[nail]	[degree]		[mm]	[mm]					[mm]			
R-RAWL-PN-3490	Pneumatic	Strip	88	34	3.8	2.8 - 4.1	50 - 90	94	8	5-7	D head nail	420x12 5x370	7.19	14.37	590667 52520 49