

RawlHAMMER

ROTARY HAMMER
SDS Plus 18 V Li-Ion
R-PRH18-26-XL2

The efficient hammer mechanism allows drilling holes in all building materials. RawlBattery's 18 V battery is interchangeable with Rawlplug 18 V devices.



FEATURES AND BENEFITS

Powerful brushless motor ensures high efficiency of the mechanism and increases the life time of the tool and three gears that regulate the rotating speed and number of impacts allows for a wide range of applications

4 functions - drilling / hammer drilling / chiseling / positioning the chisel makes the rotary hammer an extremely versatile power tool

Ergonomic mode selector allows convenient and quick switching between power tool functions







Compact design and lightweight construction reduces fatigue during long-term use

Electronic protection stop system engages during jamming to protect the user and the power tool

Two Li-Ion batteries with 5.0 Ah capacity and a 50 minute fast charger are included with the set to guarantee uninterrupted work

The SDS plus tool shank ensures full compatibility with a wide range of accessories available on the market and enables effective transfer of impact energy

BASE MATERIALS

-  Concrete
-  Reinforced concrete
-  Brick
-  Stone
-  Steel
-  Timber



The R-PRH18-26-XL2 hammer drill is characterized by a refined and durable construction. Efficient hammer mechanism allows for efficient drilling of holes in concrete and reinforced concrete up to 26 mm in diameter. The functions of shoring and setting the chisel position allow for using a power tool when chipping ceramic tiles and removing the old plaster. Two batteries and a 50-minute charger included in the set guarantee operation without unnecessary downtime.

APPLICATIONS

Drilling holes in concrete up to Ø 26 mm

Drilling holes in wood up to Ø 30 mm

Drilling holes in metal up to Ø 13 mm

Façades and roofs thermal insulations

Sheet metal drilling
up to Ø10 mm x 2 mm thick









Wooden constructions: drilling in wood
or chipboard (up to Ø 30 mm)




PRODUCT INFORMATION

| Index | Motor type | Battery voltage [V] | Battery capacity [Ah] | Rotation speed [rpm] | Impact frequency [ipm] | Impact energy [J] | Tool shank | Max drilling diameter concrete [mm] | Max drilling diameter wood [mm] | Max drilling diameter metal [mm] | Inner weight [kg] | Outer weight [kg] |
|----------------|------------|---------------------|-----------------------|----------------------------------|-------------------------------------|-------------------|------------|-------------------------------------|---------------------------------|----------------------------------|-------------------|-------------------|
| R-PRH18-26-XL2 | bushless | 18 | 5.0 | 1: 0-500 2: 0-670 3: 0-950 | 1: 0-2550 2: 0-3420 3: 0-4850 | 2.5 | SDS plus | 26 | 30 | 13 | 6.28 | 6.28 |

RELATED PRODUCTS

| | | | |
|--|---|---|---|
| <p>Drill bits Rebardrill SDS plus RT-SDSR</p>  <p>High-quality SDS plus drill bits for drilling in reinforced concrete</p> | <p>Drill bits Aggressor SDS Plus RT-SDSA</p>  <p>Drill bits SDS plus for fast drilling in concrete</p> | <p>Drill bits Brickdrill SDS plus RT-SDSB</p>  <p>Drill bits for non-impact drilling in ceramic materials</p> | <p>Hollow drill bits Dustlessdrill SDS plus RT-SDSH</p>  <p>Hollow drill bits SDS plus for dust-free drilling in concrete</p> |
| <p>Concrete screw anchor R-HLX</p>  <p>Hex Concrete Screw Anchor</p> | <p>Stainless steel Throughbolt R-HPTII-A4</p>  <p>Stainless steel throughbolt anchor for cracked and non-cracked concrete</p> | <p>Universal nylon plug with screw 4ALL</p>  <p>High performance nylon plug with screw for all types of substrates</p> | <p>Nylon frame fixing R-FF1-L</p>  <p>Universal countersunk frame fixing for many applications</p> |

OFFER

| Index | Power tool | Battery R-BAT-185001 [5.0 Ah] | Rawlcase R-RC-4414 | Box | Charger 6.5A R-CHR-186502 | Manual | Protective gloves | EAN |
|----------------|---|---|---|---|--|---|---|---|
| R-PRH18-26 |  |  |  |  |  |  |  |  |
| R-PRH18-26-XL2 | 1 | 2 | 1 | - | 1 | 1 | 1 | 5906675553917 |
| R-PRH18-26-XS | 1 | - | - | 1 | - | 1 | - | 5906675553887 |
| R-PRH18-26-S | 1 | - | 1 | - | - | 1 | - | 5906675553900 |