


## Technical data sheet



<b>Steel</b>	Chromium steel 34CrNiMo6
<b>Carbide</b>	WC-Cobalt Grade CTM17 BC
<b>Surfacing</b>	Pin shooting
<b>Carbide tip design</b>	Concrete hammering tip with centering point
<b>Tip angle</b>	160° +/- 2°
<b>Process and design of flute</b>	Fully ground half round progressive flute
<b>Attachement</b>	Compatible SDS+
<b>Hardness</b>	46 à 52 HRC
<b>Standard</b>	Produit certifié PGM
<b>Origine</b>	France

<b>Powertools</b>	SDS+ hammer less than 5Kg
<b>Materials</b>	Concrete, stone, full brick, concrete bloc

Product Code	Description			Logistic data		EAN
	Ø [mm]	L [mm]	L1 [mm]	Quantity [pcs]	Weight [kg]	
RT-SDSA-4/110	4	110	50	1	0,038	5906675114767
RT-SDSA-5/110	5	110	50	1	0,0395	5906675114774
RT-SDSA-5/160	5	160	100	1	0,039	5906675027944
RT-SDSA-5/210	5	210	150	1	0,036	5906675114781
RT-SDSA-5/310	5	310	250	1	0,15	5906675063461
RT-SDSA-5/310B12	5	310	250	12	0,76	5906675063478
RT-SDSA-5/460	5	460	400	1	0,09	5906675114798
RT-SDSA-55/160	5,5	160	100	1	0,041	5906675026503
RT-SDSA-6/110	6	110	50	1	0,037	5906675027920
RT-SDSA-6/160	6	160	100	1	0,045	5906675026589
RT-SDSA-6/160B12	6	160	100	12	0,57	5906675063539
RT-SDSA-6/210	6	210	150	1	0,045	5906675027982
RT-SDSA-6/260	6	260	200	1	0,1	5906675048598
RT-SDSA-6/310B12	6	310	250	12	0,884	5906675063485
RT-SDSA-6/460	6	460	400	1	0,09	5906675114835
RT-SDSA-7/110	7	110	50	1	0,05	5906675026572
RT-SDSA-7/160	7	160	100	1	0,049	5906675026565
RT-SDSA-8/110	8	110	50	1	0,043	5906675026558
RT-SDSA-8/160	8	160	100	1	0,056	5906675027951
RT-SDSA-8/160B12	8	160	100	12	0,679	5906675063546
RT-SDSA-8/210	8	210	150	1	0,068	5906675027968
RT-SDSA-8/260	8	260	200	1	0,068	5906675027937
RT-SDSA-8/310	8	310	250	1	0,077	5906675027975
RT-SDSA-8/310B12	8	310	250	12	0,97	5906675063508
RT-SDSA-8/410	8	410	350	1	0,137	5906675114873
RT-SDSA-8/460	8	460	400	1	0,15	5906675114880
RT-SDSA-9/160	9	160	100	1	0,071	5906675114897
RT-SDSA-10/110	10	110	50	1	0,058	5906675026596
RT-SDSA-10/160	10	160	100	1	0,069	5906675026602
RT-SDSA-10/160B12	10	160	100	12	1	5906675063553
RT-SDSA-10/210	10	210	150	1	0,09	5906675026619
RT-SDSA-10/310	10	310	250	1	0,077	5906675028002
RT-SDSA-10/310B12	10	310	250	12	1	5906675063515
RT-SDSA-10/460	10	460	400	1	0,199	5906675114910
RT-SDSA-10/610	10	610	550	1	0,261	5906675114927
RT-SDSA-10/1000	10	1000	940	1	0,54	5906675114934
RT-SDSA-12/160	12	160	100	1	0,089	5906675026633
RT-SDSA-12/210	12	210	150	1	0,112	5906675026640
RT-SDSA-12/260	12	260	200	1	0,077	5906675028019
RT-SDSA-12/310	12	310	250	1	0,168	5906675026657
RT-SDSA-12/1000	12	1000	940	1	0,54	5906675114965
RT-SDSA-14/210	14	210	150	1	0,131	5906675026664
RT-SDSA-14/260	14	260	200	1	0,167	5906675026671
RT-SDSA-14/310	14	310	250	1	0,199	5906675026688
RT-SDSA-14/460	14	460	400	1	0,25	5906675026695
RT-SDSA-14/610	14	610	550	1	0,38	5906675115009
RT-SDSA-14/1000	14	1000	940	1	0,54	5906675115047
RT-SDSA-16/260	16	260	200	1	0,207	5906675026701
RT-SDSA-16/310	16	310	250	1	0,255	5906675026718
RT-SDSA-16/460	16	460	400	1	0,302	5906675026725
RT-SDSA-16/610	16	610	550	1	0,499	5906675115085
RT-SDSA-16/1000	16	1000	940	1	0,88	5906675115092
RT-SDSA-18/310	18	310	250	1	0,315	5906675026732
RT-SDSA-18/460	18	460	400	1	0,413	5906675026749
RT-SDSA-18/610	18	610	550	1	0,66	5906675115139
RT-SDSA-18/1000	18	1000	940	1	1,105	5906675115146
RT-SDSA-20/310	20	310	250	1	0,399	5906675026756
RT-SDSA-20/460	20	460	400	1	0,529	5906675026763
RT-SDSA-22/460	22	460	400	1	0,64	5906675026770
RT-SDSA-24/460	24	460	400	1	0,735	5906675026787
RT-SDSA-25/460	25	460	400	1	0,95	5906675115245
RT-SDSA-26/460	26	460	400	1	0,866	5906675026794