

R-RAWL-PMC-38 Pneumatic joist hanger nailer

Compact pneumatic positive placement nailer for quick installation of metalconnectors



Certificate
({

Product information

Features and benefits

- Compatible with all 38 twist shank nails present on the market for freedom of choice
- Nose tip with probe mechanism locates the tool in the pre drilled hole for a precise and quick fixing. Easy to operate even in areas with limited access
- Extremely lightweight and manouverable which is an advantege when operating in areas with limited access
- Reduced risk of hand injury thanks to low recoil and low weight
- Magazine capacity 30 nails enables to limit the time needed for reloading
- Rotary belt hook provides safety and comfort during daily operation
- 360 degree rotary air connector allows for great accessibility in tight spaces

Applications

- Installation of all types of metal connectors
- Installation of truss supports and angled joints
- Installation of perforated steel tapes

Base materials

- Timber
- Wood

Corresponding products

- R-DPCG paper collated nails
- R-RAWL-C24 Oil lubricated compressor
- R-RAWL-C50 Oil lubricated compressor

Set includes

- R-RAWL-PMC-38 Pneumatic positive placement nailer
- · Spare gasket set
- Operating and Safety manual
- Safety glasses and ear plugs
- Case











Product commercial data

Index	Power source	Magazi- ne type	Magazi- ne capa- city	Magazi- ne angle	WEIGHT	Fastener diameter range	Fastener length range	Noise le- vel	Maxi- mum pressure	Opera- ting pressure	Box we- ight	Outer weight	EAN
			[nail]	[degree]	[kg]	[mm]	[mm]	[dB]	[bar]	[bar]	kg	kg	
R-RAWL-PMC-38	Pneuma- tic	Strip	29	34	2.5	3.3 - 4.1	38	94	8	5-7	4.64	23.19	59066752 51998