


Technical data sheet



Steel	Chromium steel 34CrNiMo6
Carbide	WC-Cobalt Grade CTF12 BC
Surfacing	Pin shooting
Carbide tip design	Sharpened concrete hammering tip with centering point
Tip angle	135° +/- 2°
Process and design of flute	Fully ground half round flute
Attachement	Compatible SDS+
Hardness	46 à 52 HRC
Standard	Produit certifié PGM
Origine	France

Powertools	SDS+ hammer less than 5Kg without percussion
Materials	brick wall block

Stocked range

Product Code	Description			Logistic data		EAN
	Ø [mm]	L [mm]	L1 [mm]	Quantity [pcs]	Weight [kg]	
RT-SDSB-6/260	8	260	200	1	0,3	5906675046303
RT-SDSB-8/260	8	260	200	1	0,3	5906675046310
RT-SDSB-8/310	8	310	250	1	0,3	5906675047553
RT-SDSB-8/460	8	460	400	1	0,2	5906675048918
RT-SDSB-10/260	10	260	200	1	0,3	5906675046334
RT-SDSB-10/310	10	310	250	1	0,3	5906675047560
RT-SDSB-10/460	10	460	400	1	0,2	5906675048604
RT-SDSB-12/260	12	260	200	1	0,3	5906675046341
RT-SDSB-15/260	15	260	200	1	0,3	5906675046358
RT-SDSB-16/260	16	260	200	1	0,3	5906675046365