
I®RAWLPLUG®

R-NOZ-ADAPTER

Air Adapter R-NOZ-ADAPTER







Product information

Features and benefits

- Enables precise cleaning of holes especially in deep anchoring.
- Uniform removes dust and dust from the hole.
- Thanks to the use of a compressor speed up work.
- Ideal for serial cleaning of deep holes.

Applications

- For use in a wide range of fastening applications in concrete and solid masonry structures
- Drilling holes in concrete, brick and stone
- Rebar missed-outs
- Formwork installation
- Shear dowel connections
- Renovation and modrnization
- of bridges, buildings.
- Securing formwork

Base materials

Approved for use in:

• Concrete C12/15-C50/60

Installation guide



1. Select the right air adapter to the required hole size.

- 2. Connected adapter to the flexible hose insert in the hole, reaching the bottom.
- 3. The other end of the flexible hose connect to the compressor and start cleaning the hole with dust.
- 4. Clean the hole with compressed air starting from the drill hole bottom, blow the hole at least twice by compressed air minimum 6 bar.

Product information

Product Code	Size	Description	
	D		
	[mm]	-	
R-NOZ-ADAPTER-14	14 - 20	Air adapter	
R-NOZ-ADAPTER-22	22 - 26	Air adapter	
R-NOZ-ADAPTER-28	28 - 50	Air adapter	

Product commercial data

Product Code D	Description -	Quantity [pcs]		Weight [kg]			- Bar Codes	
		Box	Outer	Pallet	Box	Outer	Pallet	Bar Codes
R-NOZ-ADAPTER- 14	Air adapter	1	30	2640	0.01	0.18	45.8	5906675447285
R-NOZ-ADAPTER- 22	Air adapter	1	30	2640	0.01	0.18	45.8	5906675447292
R-NOZ-ADAPTER- 28	Air adapter	1	30	2640	0.01	0.18	45.8	5906675447308

2