


MN-94-010 Heat gun 2000 W, 2-stage, digital

Advanced heat gun 2000 W with smooth digital temperature control



Certificates (icon):



Features & benefits

- A 2000 W heating element ensures quick start-up, efficient operation and high maximum temperature
- Two stages: the first stage provides a stable temperature at 50 deg C, the second allows temperature to be smoothly adjusted using the digital panel
- Digital panel enables smooth temperature (50 deg C to 600 deg C in 1 deg C increments) and airflow adjustment. This allows the user to set the parameters of the tool's operation suitable for the work being performed
- Adjustable airflow (150-550 liters/minute) allows the parameters of the heat gun's operation to be further adjusted to suit the work being performed
- The design of the heat gun allows it to be placed vertically as a stationary equipment and the material to be operated using both hands
- Two component rubber handle guarantees a secure and comfortable grip and makes the operation more ergonomic
- Hand guard prevents accidental burning due to the user touching the material being worked on
- Light, strong body of the heat gun means greater durability and reduced fatigue during work
- Rich set of accessories: 4 nozzles, a putty knife and a scraper, allowing a wide variety of works to be carried out without the need to buy any additional tools
- Carrying case enables easy transport of and provides convenient storage space for the tool and all its accessories
- **Red Plug Service** guarantees quick repair of a broken tool though free courier shipment from and to the customer

Applications

- Intended for the removal of paint and other paint coatings
- Intended for soft soldering of steel, copper and brass components
- Intended for forming and welding plastics
- Intended for veneering furniture and many other applications such as defrosting, drying or firing up the grill

Equipment

- 4 interchangeable tools/attachments/nozzles
- Putty knife
- Triangular scraper
- Carrying case

Users

- Varnishers
- Painters
- Carpenters
- Plumbers
- DIY enthusiasts

Technical properties

Index	Power	Box	Outer	Box weight	Outer weight	EAN
	[W]	[pcs]	[pcs]	[kg]	[kg]	
MN-94-010	2000	1	5	2.2	10.9	5906675099170

power	2000 W
temperature: level I	50 °C
temperature: level II	50-600 °C
efficiency	150 - 550 L/min
cord length	3 m

Warnings



- Read user manual
- Always use eye protection
- Always use gloves
- Always use dust mask
- **USER'S MANUAL.** Always follow safety instructions contained in the user's manual and applicable health and safety at work regulations. The failure to comply with warnings and recommendations contained therein may result in electric shock, fire, serious injuries and even death. Read and understand the user's manual carefully and keep it for future reference