

## R-RAWL-PNP-130 Pneumatic framing nailer

Pneumatic plastic strip nailer for timber framing, roofing and other timber applications



### Certificate



### Product information

#### Features and benefits

- Nail range from 90mm to 130 mm widens the range of typical applications
- Removable no mark nose for protecting the timber surface. Especially important when securing timber cladding or facades
- Magazine capacity of 50 nails provides less time needed for reloading
- Adjustable exhaust port is an important safety feature when operating in areas where other persons may be affected by the exhausted air and particles
- Simplicity of tool design ensures low maintenance and high reliability

#### Applications

- Timber frame stud work in timber framing industry
- Installation of battens and sheathing in roof construction
- Installation of wooden facades

#### Corresponding products

- R-GPG plastic collated nails
- R-RAWL-C50 Oil lubricated compressor
- R-RAWL-C50-10 Oil lubricated compressor
- R-RAWL-C100-P Oil lubricated compressor

#### Base materials

- Timber
- Plywood
- Chipboard
- Wood

#### Set includes

- R-RAWL-PNP-130 Pneumatic framing nailer
- Spare gasket set
- Operating and Safety manual
- Safety glasses



## Product commercial data

Index	Power source	Magazine type	Magazine capacity	Magazine angle	WEIGHT	Fastener diameter range	Fastener length range	Noise level	Maximum pressure	Operating pressure	Box weight	Outer weight	EAN
			[nail]	[degree]	[kg]	[mm]	[mm]	[dB]	[bar]	[bar]	kg	kg	
R-RAWL-PNP-130	Pneumatic	Strip	50	21	5.6	3.3 - 4.2	90 - 130	94	9	5-7	7.92	7.92	5906675251981