

RGU-G Emulsion Primer - Deep Penetration

Universal emulsion primer - deep penetration.

Product information



Applications

- Priming of absorbing and porous substrates.
- The perfect primer for paint, plaster, wallpaper, screeds, self-levelling floors, putty, adhesives, ceramic tiles and acrylic & mineral base-coats
- Provides a protective coating for screeds

Features and benefits

- Penetrates deep into the substrate
- Highly efficient.
- Perfectly equalizes uneven absorption of mineral substrates
- With proper application, adhesion is increased and absorbency and cohesion of the substrate are homogenized.
- Reduces the absorption of porous substrates on previously painted walls and facades
- Transparent when dry.
- Improved crack prevention, when added to adhesives.
- Does not impede the breathability of walls.
- Increases flexibility and scratch resistance

Base materials

Approved for use in:

- Concrete
- Solid Brick
- Wood
- Chipboard
- Gypsum Fibreboards
- Plasterboard

Installation guide

1. The surface, that will be primed, has to be cleaned thoroughly and degreased, the flakes of old paints should be removed.
2. Fresh cement-lime plaster can be painted not sooner than 4 weeks after application.
3. Smooth surfaces should be roughened with sandpaper. Cracks and holes should be filled up with acrylic filler, larger gaps inside buildings - with gypsum, and outside the buildings - with cement mortar.
4. Dependingly on the absorptivity of the substrate primer has to be diluted with water in proportions 1:1 or 1:2, where 1 is for primer and 2 stands for parts of water. Prior the painting the content of the container has to be mixed thoroughly.
5. Prevent occurring of brightenings and stains on the walls.

Technical Data

Parameter		Value	Methods
Range of temperatures for application	[°C]	+5 - +35	
Colour	-	colourless	
Density	[g/cm ³]	1,0	
pH value	-	8.5	
Comments	-	Suggested number of layers: 1, in particular cases: 2.	
Performance	-	10-12 m ² from 1l of product	
Drying time	[h]	1-2	
VOC Content	[g/l]	0	calculated
Storage temperature	[°C]	+5 - +35	
Shelf life	[month]	12	
RGU-05-G			
Description	-	5 l	

Product commercial data

Product Code	Description	Quantity [pcs]			Weight [kg]			Bar Codes
		Box	Outer	Pallet	Box	Outer	Pallet	
RGU-05-G	5 l	1	1	108	5.2	5.2	595.2	5906675284149