RT-SDSR DRILL BITS REBARDRILL SDS PLUS

High-quality SDS plus drill bits for drilling in reinforced concrete

FEATURES AND BENEFITS

- 3 symmetrically arranged cutting edges allow for perfectly straight and axial drilling.
- Angle tip 135° allows drilling in reinforced concrete.
- 3 material extraction surfaces and special shape of the drill facilitate the removal of dust.
- Extremely high quality, cylindricity and axial alignment of drilled holes, confirmed by international SicherSafe certificate.
- Very deep seating of carbide plate significantly improves connection with the drill core, which affects quality.
- Drilling without damaging the surface, even at the edges.
- Steel with specification 34CrNiMo6 provides high strength and durability.
- Centre point for quick commencement of drilling without the drill slipping.

SUBSTRATES

- High-density natural stone
- Concrete
- Reinforced concrete
- Solid concrete block
- Solid brick

RT-SDSR DRILL BITS REBARDRILL SDS PLUS

APPLICATIONS

Concrete structures

Masonry structures

LOGISTICAL DATA

SKU	Diameter	Length	Working length	Base-sales unit	Unit pack	Bulk pack	Single Package - Gross Weight	Bulk Package - Gross Weight	Barcode
RT-SDSR-10/110	10.0	110.0	50.0	pcs.	1.0	200.0	0.1	12.0	5906675335353
RT-SDSR-10/160	10.0	160.0	100.0	pcs.	1.0	150.0	0.1	11.7	5906675046099
RT-SDSR-10/160B12	10.0	160.0	100.0	pcs.	12.0	25.0	0.9	21.9	5906675063584
RT-SDSR-10/210	10.0	210.0	150.0	pcs.	1.0	100.0	0.1	9.8	5906675046105
RT-SDSR-10/260	10.0	260.0	200.0	pcs.	1.0	100.0	0.1	12.4	5906675046112
RT-SDSR-10/260B12	10.0	260.0	200.0	pcs.	12.0	18.0	1.3	24.7	5906675335414
RT-SDSR-10/310	10.0	310.0	250.0	pcs.	1.0	100.0	0.1	13.7	5906675046136
RT-SDSR-10/310B12	10.0	310.0	250.0	pcs.	12.0	15.0	1.6	23.8	5906675063614
RT-SDSR-10/360	10.0	360.0	300.0	pcs.	1.0	100.0	0.2	15.9	5906675387154
RT-SDSR-10/460	10.0	460.0	400.0	pcs.	1.0	100.0	0.2	19.5	5906675046143
RT-SDSR-12/160	12.0	160.0	100.0	pcs.	1.0	150.0	0.1	14.7	5906675046150
RT-SDSR-12/210	12.0	210.0	150.0	pcs.	1.0	100.0	0.1	12.1	5906675046167
RT-SDSR-12/260	12.0	260.0	200.0	pcs.	1.0	100.0	0.1	14.2	5906675046174
RT-SDSR-12/310	12.0	310.0	250.0	pcs.	1.0	100.0	0.2	17.3	5906675046181
RT-SDSR-12/460	12.0	460.0	400.0	pcs.	1.0	100.0	0.2	25.0	5906675046198
RT-SDSR-14/160	14.0	160.0	100.0	pcs.	1.0	150.0	0.1	16.9	5906675427805
RT-SDSR-14/210	14.0	210.0	150.0	pcs.	1.0	100.0	0.1	14.3	5906675046204
RT-SDSR-14/260	14.0	260.0	200.0	pcs.	1.0	100.0	0.2	17.3	5906675046211
RT-SDSR-14/310	14.0	310.0	250.0	pcs.	1.0	100.0	0.2	20.2	5906675046228
RT-SDSR-14/460	14.0	460.0	400.0	pcs.	1.0	75.0	0.3	20.7	5906675046235
RT-SDSR-15/160	15.0	160.0	100.0	pcs.	1.0	150.0	0.1	21.0	5906675335360
RT-SDSR-15/210	15.0	210.0	150.0	pcs.	1.0	100.0	0.2	18.2	5906675335377
RT-SDSR-16/160	16.0	160.0	100.0	pcs.	1.0	150.0	0.1	18.1	5906675335391
RT-SDSR-16/210	16.0	210.0	150.0	pcs.	1.0	100.0	0.2	14.8	5906675046242
RT-SDSR-16/260	16.0	260.0	200.0	pcs.	1.0	100.0	0.2	17.4	5906675046259
RT-SDSR-16/310	16.0	310.0	250.0	pcs.	1.0	60.0	0.2	13.0	5906675046266
RT-SDSR-16/460	16.0	460.0	400.0	pcs.	1.0	50.0	0.3	16.8	5906675046273
RT-SDSR-18/210	18.0	210.0	150.0	pcs.	1.0	100.0	0.2	22.1	5906675335407
RT-SDSR-18/310	18.0	310.0	250.0	pcs.	1.0	50.0	0.3	12.3	5906675046280
RT-SDSR-20/310	20.0	310.0	250.0	pcs.	1.0	40.0	0.4	13.2	5906675046297
RT-SDSR-20/460	20.0	460.0	400.0	pcs.	1.0	30.0	0.6	14.4	5906675071183
RT-SDSR-5/110	5.0	110.0	50.0	pcs.	1.0	250.0	0.0	10.4	5906675115269
RT-SDSR-5/160	5.0	160.0	100.0	pcs.	1.0	200.0	0.0	9.4	5906675046006
RT-SDSR-5/160B12	5.0	160.0	100.0	pcs.	12.0	50.0	0.5	24.2	5906675335322
RT-SDSR-5/210	5.0	210.0	150.0	pcs.	1.0	150.0	0.1	6.6	5906675115276
RT-SDSR-5/360	5.0	360.0	300.0	pcs.	1.0	150.0	0.1	10.9	5906675387123
RT-SDSR-6/110	6.0	110.0	50.0	pcs.	1.0	250.0	0.0	10.9	5906675047713
RT-SDSR-6/160	6.0	160.0	100.0	pcs.	1.0	200.0	0.0	10.2	5906675046013
RT-SDSR-6/160B12	6.0	160.0	100.0	pcs.	12.0	40.0	0.6	22.4	5906675063560
RT-SDSR-6/210	6.0	210.0	150.0	pcs.	1.0	150.0	0.1	8.7	5906675046020
RT-SDSR-6/260	6.0	260.0	200.0	pcs.	1.0	150.0	0.1	10.2	5906675046037
RT-SDSR-6/310	6.0	310.0	250.0	pcs.	1.0	150.0	0.1	10.9	5906675335346
RT-SDSR-6/310B12	6.0	310.0	250.0	pcs.	12.0	25.0	0.9	21.1	5906675063591
RT-SDSR-6/360	6.0	360.0	300.0	pcs.	1.0	150.0	0.1	12.4	5906675387130
RT-SDSR-7/160	7.0	160.0	100.0	pcs.	1.0	200.0	0.1	11.0	5906675047737
RT-SDSR-8/110	8.0	110.0	50.0	pcs.	1.0	200.0	0.0	8.4	5906675047720
RT-SDSR-8/160	8.0	160.0	100.0	pcs.	1.0	200.0	0.1	12.4	5906675046044
RT-SDSR-8/160B12	8.0	160.0	100.0	pcs.	12.0	35.0	0.7	24.2	5906675063577
RT-SDSR-8/210	8.0	210.0	150.0	pcs.	1.0	150.0	0.1	10.9	5906675046051
RT-SDSR-8/260	8.0	260.0	200.0	pcs.	1.0	100.0	0.1	8.9	5906675046068
RT-SDSR-8/310	8.0	310.0	250.0	pcs.	1.0	100.0	0.1	10.1	5906675046075
RT-SDSR-8/310B12	8.0	310.0	250.0	pcs.	12.0	20.0	1.1	22.6	5906675063607
RT-SDSR-8/360	8.0	360.0	300.0	pcs.	1.0	100.0	0.1	11.1	5906675387147
RT-SDSR-8/460	8.0	460.0	400.0	pcs.	1.0	100.0	0.1	13.8	5906675046082
RT-SDSR-8/610	8.0	610.0	550.0	pcs.	1.0	100.0	0.2	19.6	5906675483412

RT-SDSR DRILL BITS REBARDRILL SDS PLUS

RELATED PRODUCTS

DRILLING	Automatic	Cordless Hammer 18V SDS plus **R-PRH18** 	Cordless RawlHammer 18V SDS plus **R-PRH18-24** 	Cordless RawlHammer 18V SDS plus **R-PRH18-26** 	Rotary Hammer Drill SDS plus; 850W; 26mm; 2.5J **R-PRH-26850**
SAFETY	Accesories	Protective gloves for power tools **R-PGL-01-10** 			
ANCHORING		Epoxy bonded anchor **R-KEX-II** 	FF1 Frame Fixing polyamide with collar **R-FF1-N-K** 	Throughbolt **R-XPT** 	