

R-RAWL-PN-57 Pneumatic coil nailer

Pneumatic coil nailer for manufacturing pallets, wooden packaging and othe timber product







Certificate (

Product information

Features and benefits

- Nail range from 25mm to 57mm widens the range of typical applications
- Adjustable exhaust port is an improtant safety feature when operating in areas where other persons amy be affected by the exhausted air and particles
- Ergonomic design and well balanace for higher comfort of daily use and reduced risk of injury
- Nail cover from magazine to nose for safety of operation
- Very low recoil value provides great improvement in operators comfort of using the tool
- Magazine capacity up to 400 nails significantly reduces reload time
- Deasing of exhaust silencer significantly reduces noise level at the worksite

Applications

- Manufacturing pallets, packaging and external trim
- Installation of timber flooring and terraces

Base materials

- Timber
- Chipboard
- Plywood
- Wood

Corresponding products

- R-GDP wire collated nails
- R-RAWL-C50 Oil lubricated compressor
- R-RAWL-C50-10 Oil lubricated compressor
- R-RAWL-C100-P Oil lubricated compressor

Set includes

- R-RAWL-PN-57 Pneumatic coil nailer
- · Spare gasket set
- Operating and Safety manual
- · Safety glasses









Product commercial data

| Index | Power source | Magazi- ne type | ne angle | WEIGHT | Faste- ner dia- meter range | Faste- ner length range | Noise level | Maxi- mum pressure | _ | Magazi- ne capa- city | Dimen- sions | Box we- ight | Outer weight | EAN |
|--------------|-----------------|--------------------|----------|--------|--------------------------------------|----------------------------------|----------------|--------------------------|-------|-----------------------------|-----------------|-----------------|-----------------|-------------------|
| | | | [degree] | [kg] | [mm] | [mm] | [dB] | [bar] | [bar] | [nail] | [mm] | kg | kg | |
| R-RAWL-PN-57 | Pneuma- tic | Coil | 16 | 2.5 | 2.1 - 2.3 | 25 - 57 | 94 | 8 | 5-7 | 300 - 400 | 285x135 x285 | 3.63 | 18.14 | 5906675 252124 |